

INTEGRATION PERFORMANCE

IP-FORD82



The IP-FORD82 is a high-performance 2-way speaker system designed to directly replace the factory 6x8" front door speakers in your Ford F-Series truck—no modifications necessary. Installation is effortless thanks to OEM-style connectors and pre-terminated wiring that preserve your vehicle's factory wiring and warranty. No cutting, splicing, or extra steps—just plug in, bolt up, and enjoy enhanced sound.

At the core of the system is a robust 8" woofer housed within a precision-engineered die-cast aluminum bracket. This bracket not only provides a rigid and durable mounting solution but is also designed to fit perfectly into your truck's factory speaker locations. The woofer's high-efficiency design delivers deep, accurate bass response and clear midrange tones, enhancing your truck's soundstage while maintaining excellent power handling and reliability even under demanding conditions.

Complementing the woofer, Morel's 1" soft dome tweeter mounts in the factory A-pillar location using a chassis that's an exact factory match for quick snap-in installation. An included adaptor ensures compatibility with older mounting styles, fitting seamlessly across model years.

With a sensitivity of 92 dB and rated for 100W RMS, the IP-FORD82 performs strongly with your vehicle's stock amplifier and can easily handle aftermarket upgrades. Whether you're seeking a clean, straightforward audio boost or a solid foundation for a complete system overhaul, this kit delivers exceptional sound quality with plug-and-play convenience.

Key advantages

- Optimized for the F Series trucks to deliver unparalleled performance and clarity
- DirectFit plug and play - no modifications needed
- Ultra high efficiency of 92dB
- High 100WRMS power handling
- Factory mount 8" shallow woofer with die-cast chassis and inverted motor system
- Morel's soft dome tweeter (Ford)
- Designed for OEM to aftermarket amplification
- In-line crossovers for easy installation

Specifications

Woofer Size	8" shallow
Tweeter/ midrange size	Soft Dome Tweeter
Configuration	2-way
Power Handling (WRMS)	100
Peak Power (W)	200
Sensitivity (2.83V/1M) (DB)	92
Frequency Response (Hz)	40-20,000



unleash the music
www.morelhifi.com

