

TS PARAMETERS

	Supremo SE Tweeter	Supremo SE Midrange	Supremo 6SE Woofer	Supremo 9SE Woofer
Re	5.26 Ohm	4.71 Ohm	3.27 Ohm	3.54 Ohm
Le	0.028 mH	0.043 mH	0.05 mH	0.116 mH
L2	0.062 mH	0.145 mH	0.246 mH	0.676 mH
R2	1.74 Ohm	1.68 Ohm	1.68 Ohm	3.14 Ohm
Cmes	38.59 μ F	175.05 μ F	775.19 μ F	673.25 μ F
Lces	1.48 mH	18.05 mH	11.49 mH	19.26 mH
Res	14.18 Ohm	12.07 Ohm	36.93 Ohm	41.24 Ohm
fs	666.2 Hz	89.5 Hz	53.3 Hz	44.2 Hz
Mms	0.452 g	5.741 g	19.139 g	40.572 g
Mmd (Sd)	0.433 g	5.471 g	17.64 g	36.5 g
Rms	0.826 kg/s	2.717 kg/s	0.669 kg/s	1.461 kg/s
Cms	0.126 mm/N	0.55 mm/N	0.465 mm/N	0.32 mm/N
Kms	7.92 N/mm	1.82 N/mm	2.15 N/mm	3.13 N/mm
BL	3.424 N/A	5.727 N/A	4.969 N/A	7.763 N/A
Lambda s	0	0.038	0.047	0.089
Qtp	0.623	0.334	0.782	0.612
Qms	2.291	1.189	9.593	7.712
Qes	0.849	0.464	0.851	0.663
Qts	0.619	0.333	0.781	0.663
Vas	0.0078 l	1.1534 l	9.6037 l	24.9877 l
n0	0.261 %	0.172 %	0.165 %	0.313 %
Lm	86.18 dB	84.37 dB	84.19 dB	86.98 dB
Lnom	88.01 dB	85.42 dB	85.06 dB	87.5 dB
rmse Z	1.95 %	2.12 %	2.02 %	7.07 %
rmse Hx	4.3 %	2.09 %	1.51 %	2.02 %
Series resistor	0 Ohm	0 Ohm	0 Ohm	0 Ohm
Sd	6.61 cm ²	38.48 cm ²	120.76 cm ²	235.06 cm ²