



W3v3

Subwoofer Drivers

POSITION:

Excellent performance at medium power levels in compact enclosures. This classic American woofer still buries the competition in overall performance and value.



W3v3 Models:

6W3v3:
6.5-inch, 150W, 4 ohm

8W3v3:
8-inch, 250W, 4 ohm

10W3v3:
10-inch, 500W, 2 ohm or 4 ohm

12W3v3:
12-inch, 500W, 2 ohm or 4 ohm

13W3v3:
13.5-inch, 600W, 2 ohm or 4 ohm

SELLING POINTS:

#1 Ideal for Medium Power Applications

Benefits:

- Design is optimized in terms of thermal and excursion-limited power handling for the following power ranges (per woofer):
 - 6W3v3:** 35-150W RMS; **8W3v3:** 50-250W RMS
 - 10W3v3:** 100-500W RMS; **12W3v3:** 100-500W RMS
 - 13W3v3:** 125-600W RMS

#2 Very small sealed enclosure requirements

Benefits:

- Excellent sound quality and low-frequency extension in very compact enclosures:
 - 6W3v3:** 0.175 cu. ft.; **8W3v3:** 0.35 cu. ft.
 - 10W3v3:** 0.625 cu. ft.; **12W3v3:** 1.25 cu. ft.
 - 13W3v3:** 1.75 cu. ft.

#3 JL Audio Subwoofer Technology

Benefits:

- Outstanding Fidelity thanks to:
 - DMA-optimized motor systems**
= lower distortion & higher output
 - Highly linear, FEA-optimized suspension systems**
= lower distortion & high output
- Excellent Reliability thanks to innovative technologies:
 - Elevated Frame Cooling Design**
= higher power handling & output
 - Vented Reinforcement Collar (VRC)**
= higher power handling & mechanical reinforcement of critical joints
 - Integrated Spider & Terminal Ring**
= mechanical reinforcement of spider joints
 - FCAM Assembly System**
= properly aligned parts for high excursion

#4 Built in USA with Global Components

Benefits:

- **Precision Assembly and thorough Quality Control in USA**
= consistently excellent performance

TECHNOLOGIES	