

KICKER

KMTC9 & KMTC11 HORN-LOADED TOWER SYSTEMS



Seven-color RGB LED illumination

Advanced proprietary horn design with titanium tweeter for extremely smooth sound



Unique ABS/stainless-steel clamp that fits many sizes of tubes

Quick-disconnect mating socket means its easily taken down and stored away after usage

Tough polymer enclosure with UV-stable finish for years of use

Stitched polypropylene cone with Santoprene® surround

WHAT MAKES IT SUPERIOR?

- Industry-leading efficiency and SPL for loud, clear music while on the water
- Incredible low-end performance and bass extension
- 359-degree swiveling design without the need for tools
- Single-bolt removal system with no tools needed – store them away easily
- Clamps swivel to mount on curved tower bars (+/-5 degrees)

Model

KMTC9

KMTC11

| | | |
|---|---------------|----------------|
| Woofer (in, mm) | 9, 23 | 11, 28 |
| Horn Loaded Compression Driver (in., mm.) | 1, 25 | 1, 25 |
| Impedance (Ohms) | 4 | 4 |
| Continuous Power (watts RMS) | 300 | 300 |
| High Pass (dB), at Frequency (Hz) | 12, 2500 | 12, 2500 |
| Low Pass (dB), at Frequency (Hz) | 12, 2500 | 12, 2500 |
| Frequency Response (Hz) | 20-20,000 | 20-20,000 |
| Enclosure Diameter (in., mm.) | 9-13/16, 24.9 | 11-7/8, 30.2 |
| Enclosure Depth (in., mm.) | 10-7/8, 27.7 | 12-11/16, 32.3 |
| Enclosure Height (in., mm.) | 11-9/16, 29.4 | 13-5/8, 34.6 |
| Total Enclosure Height (in., mm.) | 13-9/16, 34.4 | 15-9/16, 39.6 |

*From Bottom Of Roll Bar

**From Top Of Bracket To Bottom Of Enclosure

