KKICKER

$oldsymbol{\mathsf{COMPRT}}^{ extstyle{ extstyle{\mathsf{R}}}}$ thin loaded enclosures

Dual Voice Coils and Unique Heat Management for a Thin but Powerful Sub



Less than Seven Inches Deep to Fit Most Anywhere

WHAT MAKES IT SUPERIOR?

- -Active Thin-Mount CompRT® Subwoofer Paired with Passive ReFLEX™ Sub for Deep Bass
- -Compact Enclosures with Tough MDF Construction for Behind or Under the Seat
- -Passive ReFLEX™ Subwoofer Provides Deep, Smooth Bass in an Incredibly Thin Box

Model	TCWRT12	TCWRT10	TCWRT8	TCWRT67
Woofers (in, cm)	12, 30	10, 25	8, 20	6-3/4, 173
Impedance (Ohms)	2 or 4	2 or 4	2 or 4	2 or 4
Recommended Amp Power (watts RMS)	500	400	300	150
Peak Power Handling (watts)	1000	800	600	300
Sensitivity (dB 1w/1m)	85.5	84.8	81.8	82.6
Enclosure Top Depth (in, cm)	3-1/2, 8.9	3-7/16, 8.8	3-9/16, 9	3-5/16, 8.5
Enclosure Bottom Depth (in, cm)	7, 17.7	6-9/16, 16.7	6-7/16, 16.4	5-11/16, 14.5
Enclosure Height (in, cm)	13-1/2, 34.3	11-13/16, 30	11-7/16, 29.1	10, 25.4
Enclosure Width (in, cm)	27, 68.5	23-1/4, 59.1	19-5/16, 49	15-1/4, 38.7