## **MKICKER**.

Sturdy, Spring-Loaded Wire Terminals


## ADVANCED SUBWOOFERS

Ribbed Santoprene® Surround Provides Large Excursion and Distortion-Free Bass

Rigid SoloKon™ Cone System with 360-Degree Bracing







Voice Coil Heat is Forced out of the Woofer As Cone Moves Downward, the Hot Air is Forced out of the Woofer. When the Cone Moves up, it Draws in Cool Outside Air.

## WHAT MAKES IT SUPERIOR?

- -New and Improved KICKER's Workhorse Bass-maker
- -Features Forced-Air Cooling™ 25% Cooler for Increased Reliability
- -Legendary CompR Subwoofer is the Model of Power and Durability

Model	CWR15	CWR12	CWR10	CWR8
Woofers [in, cm]	15, 38	12, 30	10, 25	8, 20
Impedance [Ohms]	2 or 4	2 or 4	2 or 4	2 or 4
Rec. Amp Power [watts RMS]	800	500	400	300
Peak Power Handling [watts]	1600	1000	800	600
Frequency Response [Hz]	25-500	25-500	30-500	30-500
Sensitivity [dB 1w/1m]	89.4	86.9	84.6	82.1
Mounting Depth [in, cm]	7-15/16, 20.1	5-3/4, 14.5	5-1/4, 13.3	4-1/8, 10.5
Xmax [Linear Excursion] [mm]	14.5	14	14	10.5

FOR MORE INFO: www.kicker.com