



Less than 5 Inches Deep

Dual Voice Coils for Installation Flexibility




Unique Heat Management

for a Thin but Powerful Sub

Stitched Surround for Unsurpassed Reliability

WHAT MAKES IT SUPERIOR?

-New and Improved – True Subwoofer Performance from a Thin Driver -Features Forced-Air Cooling[™] - 20% Cooler for Increased Reliability -Legendary KICKER Bass in a Thin Subwoofer



As Cone Moves Downward, the Hot Air is Forced out of the Woofer. When the Cone Moves up, it Draws in Cool Outside Air.

Model	CWRT12	CWRT10	CWRT8	CWRT67
Woofers [in, cm]	12, 30	10, 25	8, 20	6-3/4, 16.5
Impedance [Ohms]	2 or 4	2 or 4	2 or 4	2 or 4
Rec. Amp Power [watts RMS]	500	400	300	150
Peak Power Handling [watts]	1000	800	600	300
Frequency Response [Hz]	25-500	25-500	30-500	30-500
Sensitivity [dB 1w/1m]	85.5	84.8	81.8	82.6
Mounting Depth [in, cm]	3-3/4, 9.6	3-7/16, 8.8	2-11/16, 6.7	2-3/4, 6.9
Xmax [Linear Excursion] [mm]	10.5	10.5	8	5.1

FOR MORE INFO : www.kicker.com