



link mini-amps

Ultimate Integration Performance Value

All Wavtech DNA • Summing • Thermal Management • Stop-Start Ready



link300.4mini

Power:

- 75Wx4 (2Ω)
- 150Wx2 (4Ω BTL)
- 50Wx4 (4Ω)

Chassis Size:

- 1.65"x4.5"x6.4"
- 42x115x163mm



link500.1mini

Power:

- 500Wx1 (2Ω)
- 300Wx1 (4Ω)

Chassis Size:

- 1.65"x4.5"x9.6"
- 42x115x243mm



link1000.1mini

Power:

- 1000Wx1 (2Ω)
- 600Wx1 (4Ω)

Chassis Size:

- 1.65"x4.5"x11.9"
- 42x115x303mm

4-Channel Features:

- Independent Input Channel Select (Direct, Copy and Sum)
- 2-way Summing with All Channel Output
- Variable 12dB/oct. HP/LP Filters (50-500Hz)
- +/-6dB Level Trim for Output Adjustment after Summing
- Bridgeable for 3-channel or 2-Channel Operation



Mono Features:

- Fully Adjustable Parametric EQ (Boost, Width and Freq)
- Variable 24dB/oct. LP Filter (50-500Hz)
- Variable 24dB/oct. Subsonic Filter (5-50Hz)
- Dual Mono Output Terminals
- RLC Ready (linkRC)



Common Features:

- Differential Balanced Inputs
- Ideal Gain with Dual Input Range and Clip LED(s)
 - RCA Input 200mV-5V, 400mV-10V
 - Spk Input: 800mV-20V, 1.6V-40V
- Built-in Loading for OEM Load Detect
- Auto Turn-on via DC Offset and/or Audio Detect
- Multi-Stage Thermal Management
- Stop-Start Vehicle Ready
- 4AWG Power/Ground Insert Terminals
- 12AWG Speaker Insert Terminals
- Speaker Level Inputs with Locking Detachable Terminals
- Panel-mount RCA Inputs with Selectable Bal/Unbal Operation
- Ultra-Compact Aluminum Chassis with Detachable Mounting Tabs

