



MicroSub+™

Amplified, Slot-Ported Systems

Position:

Uniting a proprietary amplifier design with JL Audio's legendary slot-ported enclosures to create all-in-one bass solutions capable of astonishing output and efficiency.

FEATURES:

- Slot-ported enclosure designs pair our exclusive DCD™ amplifier and low-impedance drivers
- Flared slot-port design minimizes turbulence and improves fidelity
- Flexible input section accepts line-level or speaker-level outputs
- 12dB/oct. low-pass filter with 50-200 Hz variable frequency selection
- Automatic turn-on options via Signal-Sensing or DC-Offset sensing
- Remote level control with optional controller (RBC-1)
- High-quality black carpet with embroidered logo
- Steel mesh woofer grille provides woofer protection
- 2-Year Warranty (Note: Warranty terms may differ outside of USA.)
- Enclosures and Subwoofer Drivers Built in USA



W3v3 Models:

ACP108LG-W3v3:

Single 8W3v3, ported enclosure,
Built-in 250W amplifier

ACP208LG-W3v3:

Dual 8W3v3, ported enclosure,
Built-in 500W amplifier

TW1 Low-Profile Models:

ACP110LG-TW1:

Single 10TW1, ported enclosure,
Built-in 400W amplifier

ACP112LG-TW1:

Single 12TW1, ported enclosure,
Built-in 400W amplifier





MicroSub™

Slot-Ported Systems

Position:

A unique solution for tight spaces, integrating a highly capable W3v3 or TW1 driver into a very low-profile, slot-ported design. Excellent sound quality and surprising output capability with moderate power.

FEATURES:

- Flared slot-port design minimizes turbulence and improves fidelity
- Very low-profile enclosure design
- High-quality black carpet with embroidered logo
- Steel mesh woofer grille provides woofer protection
- Gold-plated, five-way binding post terminal
- 2-Year Warranty (Note: Warranty terms may differ outside of USA.)
- Enclosures and Subwoofer Drivers Built in USA



W3v3 Models:

CP106LG-W3v3:

Single 6W3v3, ported enclosure, 150W, 4 ohm

CP108LG-W3v3:

Single 8W3v3, ported enclosure, 250W, 4 ohm

CP208LG-W3v3:

Dual 8W3v3, ported enclosure, 500W, 2 ohm

TW1 Low-Profile Models:

CP110LG-TW1:

Single 10TW1, ported enclosure, 300W, 2 ohm or 4 ohm

CP112LG-TW1:

Single 12TW1, ported enclosure, 300W, 2 ohm

