

Internal 12dB/Octave Crossovers for Superior Smoothness and Protection

MSS Features a Component System Design for Increased Mounting Options and Sonic Accuracy

UMAP \$499.99 – \$699.99
Shipping Fourth Quarter

MSC is a High-Performance, Drop-In Replacement for Existing Speaker Holes

Marine Standard Electrical Plugs for Lighting and Speaker Connections

Carbon-Fiber-Infused Midrange Woofers for Accurate Sound Reproduction

UV-Resistant, 28mm Teton®-Dome Audiophile Tweeters

Glass-Infused Nylon Basket Frames for Outstanding Thermal Performance

Includes Both Charcoal and White Grille Pairs

Customizable RGBW LED Lighting to Match Your Theme or Mood

WHAT MAKES IT SUPERIOR?

- KICKER's New Standard in Audio Performance and Durability
- Real Marine® Maximum Weather, Corrosion, and UV Resistance
- KICKER Signature Sound Quality and Reliability

Select color, brightness, fade or strobe with a KICKER Lighting Controller (sold separately)



MODEL	MSS8	MSS65	MSC8	MSC65
Woofers (in, mm)	8, 200	6-1/2, 165	8, 200	6-1/2, 165
Tweeters (in, mm)	1-1/8, 28	1-1/8, 28	1-1/8, 28	1-1/8, 28
Rated Impedance (Ohms)	4	4	4	4
Recommended Amp Power (watts RMS)	15-200	15-100	15-200	15-100
Peak Power Handling (watts)	400	200	400	200
Frequency Response (Hz)	45-25k	55-25k	45-25k	55-25k
Sensitivity (dB 1w/1m)	90.5	89	90.5	89
Woofer Mounting Hole Diam. [in, mm]	6-9/16, 167	5-7/16, 139	6-9/16, 167	5-7/16, 139
Woofer Bottom Mount Depth [in, mm]:	3-1/2, 89	3-1/4, 83	3-1/2, 89	3-1/4, 83
Flush Mount Tweeter Hole Diam. [in, mm]:	2, 51	2, 51	—	—
Flush Mount Tweeter Depth [in, mm]:	2-1/8, 55	2-1/8, 55	—	—
Internally Mounted Crossover:	12dB/octave, high pass at 3.2kHz	12dB/octave, high pass at 3.2kHz	12dB/octave, high pass at 3.2kHz	12dB/octave, high pass at 3.2kHz
Grilles	charcoal and white	charcoal and white	charcoal and white	charcoal and white

